

Order form	
Orderer	

Valid from

DPT145 Multiparameter transmitter for SF6 gas

		1 2 3 4	5 6	7 8	9 1	0 11	
	Vaisala Multiparameter T	ransmitter DPT145 A A A A	Α				PRICE
1	Probe	DPT145 base - probe with UNF 7/8- 14 thread A					
2	Measurement parameters	Td/f, Td/f atm, ppm, P, Pnorm, density and T for SF6 gas					
		Td/f, Td/f atm, ppm, P, Pnorm, density and T for mixed SF6/N2 gas, %SF6%N2 2					
3	Digital output	RS485 A					
4,5	Reserved codes	A A	Α				
5	Output units	Metric units (Celsius, bara)	1				
		Non-metric units (Fahrenheit, psia)	2				
7	Mechanical connection	DILO DN20 connector		В			
		ABB connector		С			
		Alstom connector		D			
3	Cable for RS485 output	None		0			
	and power supply	1,5 m Shielded PUR cable with 90°connector		1			
		3 m Shielded PUR cable with 90°connector		2			
		5 m Shielded PUR cable with 90°connector		3			
		10 m Shielded PUR cable with 90°connector		4			
		3 m Shielded FEP cable with straight connector (Compatible w. combination of Alstom connector + Rain shield)		5			
9	Installation accessories	None			0		
		Weather shield			1		
10	Special features	None			Α	_	
11	User' s guide	None				Α	
		Multilingual quick guide				Х	
	•					Total	
					Total v	/alue	

Selections in bold are included in the prices of the basic versions.

Connection cable for DM70

Selections in italic are available at an extra price.

End customer:

Accessories and spare parts 219980

219690 USB Serial Interface Cable 218675SP Protection plug for connector 231519SP 1.5 m Shielded PUR cable with 90° connector 231520SP 3 m Shielded PUR cable with 90°connector 231521SP 5 m Shielded PUR cable with 90°connector 231522SP 10 m Shielded PUR cable with 90°connector 3 m Shielded FEP cable with straight connector Weather shield

226902SP ASM210326SP