

HMT130 Temperature Transmitter

| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | Price |
|---|---|---------------------|------------------------|----------|----------|---|---|----------|----------|----------|----------|----------|----------|----------|-------------|-------|
| Vaisala HUMICAP® Temperature Transmitter | | HMT130 | | T | | | | A | 0 | | | | | | | |
| 1 Output parameters | Temperature output only | | | T | | | | | | | | | | | | |
| 2 Transmitter type | Wall mount/fixed probe | | | A | | | | | | | | | | | | |
| | <i>Remote probe with 3 m cable</i> | | | B | | | | | | | | | | | | |
| | <i>Remote probe with 5 m cable</i> | | | C | | | | | | | | | | | | |
| | <i>Remote probe with 10 m cable</i> | | | D | | | | | | | | | | | | |
| | <i>Remote probe with 10 m cable + 10 m extension</i> | | | E | | | | | | | | | | | | |
| 3 Display | No display | | | 0 | | | | | | | | | | | | |
| | <i>Display</i> | | | 1 | | | | | | | | | | | | |
| 4 Output signal | 0...1 V | 3-wire | | | B | | | | | | | | | | | |
| | 0...5 V | 3-wire | | | C | | | | | | | | | | | |
| | 0...10 V | 3-wire | | | D | | | | | | | | | | | |
| SPECIAL | Define scale: | 3-wire | _____ V *) | | X | | | | | | | | | | | |
| 5 Parameter for Output 1 | T | -40...+60 °C | (-40...+140 °F) | | B | | | | | | | | | | | |
| | | -20...+80 °C | (-4...+176 °F) | | C | | | | | | | | | | | |
| | | 0...+60 °C | (+32...+140 °F) | | D | | | | | | | | | | | |
| | | -40...+80 °C | (-40...+176 °F) | | E | | | | | | | | | | | |
| SPECIAL | Define quantity | _____ | Scale | _____ | X | | | | | | | | | | | |
| 6 Parameter for Output 2 | None | | | | A | | | | | | | | | | | |
| 7 | | | | | 0 | | | | | | | | | | | |
| 8 Display Units | Metric | | | | | | | | 1 | | | | | | | |
| | Non metric | | | | | | | | 2 | | | | | | | |
| 9 Sensor protection | Plastic grid | | | | | | | | | 1 | | | | | | |
| | Plastic grid with PTFE filter | | | | | | | | | 2 | | | | | | |
| | Stainless steel sintered filter (for remote probes only) | | | | | | | | | 3 | | | | | | |
| 10 Transmitter installation | No accessories | | | | | | | | | | A | | | | | |
| | <i>Rain shield with installation kit (215109)</i> | | | | | | | | | | C | | | | | |
| 11 Installation kit for probe | No accessories | | | | | | | | | | | 1 | | | | |
| | <i>Duct installation kit (215619)</i> | | | | | | | | | | | 2 | | | | |
| | <i>Probe mounting flange (226061)</i> | | | | | | | | | | | 3 | | | | |
| | <i>Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)</i> | | | | | | | | | | | 5 | | | | |
| 12 Cable bushings | Cable gland for 2...6 mm diameter cable | | | | | | | | | | | | A | | | |
| | Conduit fitting PG9 | | | | | | | | | | | | B | | | |
| | Conduit fitting NPT 1/2" | | | | | | | | | | | | C | | | |
| | No bushing (rubber plug) | | | | | | | | | | | | D | | | |
| | <i>All bushings (includes A, B, C and D)</i> | | | | | | | | | | | | Z | | | |
| 13 PC Accessories | No | | | | | | | | | | | | | 0 | | |
| | <i>Service cable for PC, USB (219685)</i> | | | | | | | | | | | | | 1 | | |
| 14 Operation manual | No manual | | | | | | | | | | | | | | A | |
| | Multilingual | | | | | | | | | | | | | | Z | |
| | | | | | | | | | | | | | | | Total | |
| | | | | | | | | | | | | | | | QTY | |
| | | | | | | | | | | | | | | | Total value | |

*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT130 T A 1 D B A 0 1 1 A 1 A 0 Z