

## HMT120 Humidity and Temperature Transmitter

		1	2	3	4	5	6	7	8	9	10	11	12	13	Price
<b>Vaisala HUMICAP® Humidity and Temperature Transmitter</b>		<b>HMT120</b>				<b>A</b>									
1	<b>Output parameters</b>	<b>Humidity output only</b>		<b>H</b>											
		<b>Humidity and temperature output</b>		<b>K</b>											
2	<b>Transmitter type</b>	<b>Wall mount/fixed probe</b>		<b>A</b>											
		<i>Remote probe with 3 m cable</i>		<b>B</b>											
		<i>Remote probe with 5 m cable</i>		<b>C</b>											
		<i>Remote probe with 10 m cable</i>		<b>D</b>											
		<i>Remote probe with 10 m cable + 10 m extension</i>		<b>E</b>											
3	<b>Display</b>	<b>No display</b>		<b>0</b>											
		<i>Display</i>		<b>1</b>											
4	<b>Output signal</b>	<b>4...20 mA</b>	<b>2-wire loop-powered</b>		<b>A</b>										
5	<b>Parameter for Output 1</b>	<b>RH</b>	<b>0...100 %RH</b>		<b>1</b>										
		<b>Tdf</b>	<b>-20...+80 °C</b> (-4...+176 °F)		<b>2</b>										
		<b>h</b>	<b>-40...1500 kJ/kg</b> (-9.5...+652.6 Btu/lb)		<b>3</b>										
		<b>Tw</b>	<b>0...+80 °C</b> (+32...+176 °F)		<b>4</b>										
	<b>SPECIAL</b>	<b>Define quantity</b>	<b>Scale</b>		<b>X</b>										
6	<b>Parameter for Output 2</b>	<b>None</b>			<b>A</b>										
		<b>T</b>	<b>-40...+60 °C</b> (-40...+140 °F)		<b>B</b>										
			<b>-20...+80 °C</b> (-4...+176 °F)		<b>C</b>										
			<b>0...+60 °C</b> (+32...+140 °F)		<b>D</b>										
			<b>-40...+80 °C</b> (-40...+176 °F)		<b>E</b>										
			<b>0...+50 °C</b> (+32...+122 °F)		<b>F</b>										
	<b>SPECIAL</b>	<b>Define scale</b>			<b>X</b>										
7	<b>Display Units</b>	<b>Metric</b>			<b>1</b>										
		<b>Non metric</b>			<b>2</b>										
8	<b>Sensor protection</b>	<b>Plastic grid</b>			<b>1</b>										
		<b>Plastic grid with PTFE filter</b>			<b>2</b>										
		<b>Stainless steel sintered filter (for remote probes only)</b>			<b>3</b>										
9	<b>Transmitter installation</b>	<b>No accessories</b>			<b>A</b>										
		<i>Rain shield with installation kit (215109)</i>			<b>C</b>										
10	<b>Installation kit for probe</b>	<b>No accessories</b>			<b>1</b>										
		<i>Duct installation kit (215619)</i>			<b>2</b>										
		<i>Probe mounting flange (226061)</i>			<b>3</b>										
		<i>Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)</i>			<b>5</b>										
11	<b>Cable bushings</b>	<b>Cable gland for 2...6 mm diameter cable</b>			<b>A</b>										
		<b>Conduit fitting PG9</b>			<b>B</b>										
		<b>Conduit fitting NPT 1/2"</b>			<b>C</b>										
		<b>No bushing (rubber plug)</b>			<b>D</b>										
		<i>All bushings (includes A, B, C and D)</i>			<b>Z</b>										
12	<b>PC Accessories</b>	<b>No</b>			<b>0</b>										
		<i>Service cable for PC, USB (219685)</i>			<b>1</b>										
13	<b>Operation manual</b>	<b>No manual</b>			<b>A</b>										
		<b>Multilingual</b>			<b>Z</b>										
														Total	
														QTY	
														Total value	

Selections in bold are included in the prices of the basic versions  
Selections in italic are available at an extra cost

Example of order code with typical settings

<b>HMT120</b>	<b>K</b>	<b>A</b>	<b>0</b>	<b>A</b>	<b>1</b>	<b>B</b>	<b>1</b>	<b>1</b>	<b>A</b>	<b>1</b>	<b>A</b>	<b>0</b>	<b>Z</b>
---------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------