

Order form Orderer Valid from February 2008 Order no.

## **MMT318 Moisture and Temperature Transmitter**

Vaisala HUMICAP <sup>®</sup> Mois			MMT310	8		A	+	<u> </u>	$\vdash$	_	-	$ \rightarrow$	2	1	'	2	PRICE
Probe code MMT31		pelines		8													
Transmitter type Mounting	aw+T			F													
	aw+T+ppm	for mineral transformer oil only	V	М													
	aw+T+ppm**)	specific transformer oil type:		. X													
	Mounting plate (72.5	x 115 mm)			5 6												
	Mounting plate (48.5	Mounting plate (48.5 x 115 mm)															
Power supply	no (24 VDC)					Α											
Signal output	Analog output chann	el (Ch1&Ch2)	4 20 mA &	RS232C		1											
	Analog output chann	0 20 mA &	RS232C		2												
Analog output signals	Analog outputs disal	bled					Α	Α									
or Ch1 and Ch2	Temperature (choose	e range in next section)					С	с									
	aw (01)	(01)					т	т									
	ppm (0100)	(0100)					U	U									
SPECIAL: Define quantity	for CH1:	CH2:					х	х									
Define scale	for CH1:	CH2:															
NOTE:																	
- Choose A for both channels			Ch1														
when you don't use analog outputs			Ch2					-									
Analog output range	No range								Α								
or temperature	-60…+60 ℃	(-76140°F)							в								
	-40+60 °C	(-40+140°F)							с								
	-40+120 ℃	(-40+248 °F)							D								
	-40+180 ℃	(-40+356°F)							Е								
	-20+60 ℃	(-4+140°F)							F				_ I				
	-20+80 °C	(-4+176°F)							G								
	-20+120 °C	(-4+248 °F)							н								
NOTE:	0+60°C	(+32+140°F)							J								
- Choose A when T	0+100 <i>°</i> C	(+32+ 212°F)							ĸ								
is not desired	special	(							x				_ I				
Output units Interface connection Operating manual language	metric									1							
	non-metric									2							
	Connector (M12, 8-pi	n) no plug															
		Connector (M12, 8 pin) and plug with 5m cable								4							
		and plug with screw terminals								5							
	no manual	, and plug min solew certilindis								č	A		_ I			(	
g manaan angaago	english										В						
Probe type	215 mm probe	with 2 m cable										s	_ I				
	215 mm probe	with 5 m cable										T					
	215 mm probe	with 10 m cable										Ū	_ I				
	400 mm probe	with 2 m cable										v	_ I				
	400 mm probe	with 5 m cable										W					
	400 mm probe	with 10 m cable										Ζ					
Moisture sensor type	special sensor for flu												2	_			
Sensor protection in probe		or applications with high flow sp	eed, >1 m/s)											E			
	stainless steel grid (	standard)												<u>F</u>			
- Installation kit	ball valve set													1	E		
														G			
	fitting body ISO1/2, r fitting body NPT1/2, r														G H		
	$\mu t n a poav NP 11/2.1$	IO IEAK SCIEW													н	1	
Veliburation contificate																' <u>,</u> I	
Calibration certificate	calibration at room to															2 DTAL	

QTY TOTAL VALUE

Selections in bold are included in the prices of the basic versions. Selections in italic are available at an extra price.

Example of order code with typical settings:

MMT310 8 F 5 A 1 C T K 1 4 B S 2 F 1 E 2

End customer:

\*\*) Check the availability and special delivery time from your local Vaisala representative. This model is always needed with silicone based transformer oils.